

Thermostats—Electromechanical Non-Programmable

Q674 Thermostat Subbases

Provide wiring terminals, mounting base, and system and fan switching for T874 Multi-stage Thermostats.



- Mount on wall or horizontal outlet box.
- Adapter plate is available for mounting on vertical outlet box (see Parts and Accessories at the end of this section).

- Subbases available without LED (light emitting diode) or with one LED.

ELECTRICAL RATINGS:

Contacts: 2.5A at 30 Vac (7.5A inrush).

Display, LED: 30 Vac (optional).

DIMENSIONS, APPROXIMATE: 3⁹/₁₆ in. (91 mm) high, 5⁵/₈ in. (143 mm) wide, 5¹/₁₆ in. (8 mm) deep.

ACCESSORIES:

See Parts and Accessories at the end of this section.

Thermostat Guards: See Index for page numbers.

*TRADELINE models.

Order Number ^a	Switch Positions		Display, LED	Use With	Terminal Designations	Comments
	System	Fan				
*Q674A1019	HEAT-AUTO-COOL	AUTO-ON	—	T874A-D	R _H ,R _C ,Y ₁ ,Y ₂ ,W ₁ ,W ₂ ,G	—
Q674B1018 ^c	HEAT-OFF-COOL	AUTO-ON	—	T874A-D (For electric heat applications.)	R _H ,R _C ,Y ₁ ,Y ₂ ,W ₁ ,W ₂ ,G,O,B	Use with C815A1004 for outdoor reset.
*Q674B1034					R _H ,R _C ,Y ₁ ,Y ₂ ,W ₁ ,W ₂ ,G,O,B	
Q674B1075 ^b					R _H ,R _C ,Y ₁ ,Y ₂ ,W ₁ ,W ₂ ,G,O,B	
Q674B1216					R _H ,R _C ,Y ₁ ,Y ₂ ,W ₁ ,W ₂ ,G,O,B,T	
*Q674C1058	OFF-AUTO	AUTO-ON	1	T874A-F	R _H ,R _C ,Y ₁ ,Y ₂ ,W ₁ ,W ₂ ,G,O,B	—
*Q674D1040	None			None	R _H ,R _C ,Y ₁ ,Y ₂ ,W ₁ ,W ₂	
*Q674E1049	OFF-HEAT-AUTO-COOL			T874A-D	R _H ,R _C ,Y ₁ ,Y ₂ ,W ₁ ,W ₂ ,G,O,B ^d	
*Q674E1403	OFF-HEAT-AUTO-COOL			T874D1942	R _H ,R _C ,W ₁ ,W ₂ ,Y ₁ ,Y ₂ ,G,O,B	
Q674F1022	OFF-EM.HT.-HEAT-AUTO-COOL	None	2	T874C,D	R _H ,Y ₁ ,Y ₂ ,W ₁ ,W ₂ ,G,O,B,E,X ₁ ,X ₂ ^d	Includes field-selectable inserts for LED.
Q674F1212	OFF-COOL-AUTO-HEAT-EM.HT.			T874G1246 only.	R _H ,Y ₁ ,W ₂ ,W ₃ ,G,O,E,L,X	
Q674F1220				T874N1016 only.	R _H ,W ₁ ,W ₂ ,G,L,C,K,X	
*Q674F1410	OFF-EM.HT.-HEAT-AUTO-COOL			T874G1246 only.	R _H ,Y ₁ ,W ₁ ,W ₂ ,W ₃ ,G,O,B,E,L,X	
*Q674F1436	OFF-EM.HT.-HEAT-AUTO-COOL	None	1	T874G1626	R _H ,Y ₁ ,W ₂ ,G,B,E,L,X	Changeover in heating mode.
*Q674F1543	OFF-EM.HT.-HEAT-AUTO-COOL	AUTO-ON	1	T874D	R _H ,W ₁ ,W ₂ ,Y ₁ ,Y ₂ ,G,E,B,X	Replaces York model no. 2TB04700524 (Q674F1451).
*Q674G1070	OFF-AUTO	None	—	T874A-F	R _H ,R _C ,Y ₁ ,Y ₂ ,W ₁ ,W ₂ ,O,B	—
Q674J1043	EM.HT.-AUTO-OFF	AUTO-ON	2	T874G1204	R _H ,Y ₁ ,W ₁ ,G,O,B,F,T,X ₂	Replaces GE AY28X077 and AY28X138.
Q674K1026	OFF-WOOD-WOOD/OIL-OIL	None	—	T874F1155 only.	R _H ,W ₁ ,W ₂ ,X	Replaces Q674K1018, GE AY28X139 and AY28X078.
Q674L1207	EM.HT.-HEAT-OFF-COOL	AUTO-ON	2	T874R1152 only.	R _H ,Y ₁ ,W ₂ ,W ₃ ,G,O,B,E,L,X	—

^a You may also want to contact your Honeywell Sales Representative and/or consult the T874/Q674 specification sheet, Honeywell form 60-2485, for replacement information and internal circuitry of specific models.

^b Auto fan on both heat and cool. For electric heat applications.

^c With isolated fan.

^d O and B terminals are continuously energized in the AUTO mode.