

**1 PRODUCT AND COMPANY IDENTIFICATION****Fluorochemicals**

2000 Market Street

Philadelphia, PA 19103

Information Telephone Numbers

EMERGENCY PHONE NUMBERS:

Chemtrec: (800) 424-9300 (24hrs) or (703) 527-3887

Medical: Rocky Mountain Poison Control Center
(303) 623-5716 (24Hrs)

Phone Number

Available Hrs

Product Information

800-245-5858

8:00 am - 5:30 pm (Eastern)

Product Name Forane (R) 502

Product Synonym(s)

Chemical Family Hydrogenated Chlorofluorocarbon/ Chlorofluorocarbon Blend

Chemical Formula Mixture

Chemical Name Chlorodifluoromethane (HCFC - 22)/Chloropentafluoroethane (CFC - 115)

EPA Reg Num

Product Use Refrigerant

2 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	CAS RegistryNumber	Typical Wt. %	OSHA
Chloropentafluoroethane (CFC-115)	76-15-3	51.2%	Y
Chlorodifluoromethane	75-45-6	48.8%	Y

The substance(s) marked with a "Y" in the OSHA column, are identified as hazardous chemicals according to the criteria of the OSHA Communication Standard (29 CFR 1910.1200)

This material is classified as hazardous under Federal OSHA regulation.

The components of this product are all on the TSCA inventory list.

3 HAZARDS IDENTIFICATION**Emergency Overview**

Colorless liquified gas with faint ether odor.

WARNING!

LIQUID AND GAS UNDER PRESSURE, OVERHEATING AND OVERPRESSURIZING MAY CAUSE GAS RELEASE OR VIOLENT CYLINDER BURSTING. MAY DECOMPOSE ON CONTACT WITH FLAMES OR EXTREMELY HOT METAL SURFACES TO PRODUCE TOXIC AND CORROSIVE PRODUCTS. VAPOR REDUCES OXYGEN AVAILABLE FOR BREATHING AND IS HEAVIER THAN AIR. HARMFUL IF INHALED AND MAY CAUSE HEART IRREGULARITIES, UNCONSCIOUSNESS OR DEATH. LIQUID CONTACT WITH EYES OR SKIN MAY CAUSE FROSTBITE.

Potential Health Effects

Skin contact and inhalation are expected to be the primary routes of occupational exposure to this material. As with most liquified gases, contact with the rapidly volatilizing liquid can cause frostbite to any tissue. High vapor concentrations are irritating to the eyes and respiratory tract and may result in central nervous system (CNS) effects such as headache, dizziness, drowsiness and, in severe exposure, loss of consciousness and death. The dense vapor of this material may reduce the available oxygen for breathing. Prolonged exposure to an oxygen-deficient atmosphere may be fatal. Inhalation may cause an increase in the sensitivity of the heart to adrenaline, which could result in

irregular or rapid heartbeats. Medical conditions aggravated by exposure to this material include heart disease or compromised heart function.

4 FIRST AID MEASURES

IF IN EYES, immediately flush with plenty of water. Get medical attention if irritation persists.

IF ON SKIN, Flush exposed skin with lukewarm water (not hot), or use other means to warm skin slowly. Get medical attention if frostbitten by liquid or if irritation occurs.

IF SWALLOWED, Not applicable - product is a gas at ambient temperatures.

IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. Do not give adrenaline, epinephrin or similar drugs following exposure to this product.

5 FIRE FIGHTING MEASURES

Fire and Explosive Properties

Auto-Ignition Temperature	NA	
Flash Point	NA - GAS	Flash Point Method
Flammable Limits- Upper	NA	
Lower	NA	

Extinguishing Media

Use extinguishing media appropriate to surrounding fire conditions.

Fire Fighting Instructions

Stop the flow of gas if possible. Use water spray on person making shut-off. Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand NIOSH approved or equivalent). Fire fighting equipment should be thoroughly decontaminated after use.

Fire and Explosion Hazards

May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products. Liquid and gas under pressure, overheating or overpressurizing may cause gas release and/or violent cylinder bursting. Container may explode if heated due to resulting pressure rise. Some mixtures of HCFCs and/or HCFs, and air or oxygen may be combustible if pressurized and exposed to extreme heat or flame.

6 ACCIDENTAL RELEASE MEASURES

In Case of Spill or Leak

Use Halogen leak detector or other suitable means to locate leaks or check atmosphere. Keep upwind. Evacuate enclosed spaces and disperse gas with floor-level forced-air ventilation. Exhaust vapors outdoors. Do not smoke or operate internal combustion engines. Remove flames and heating elements.

7 HANDLING AND STORAGE

7 HANDLING AND STORAGE

Handling

Avoid breathing gas. Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Do not enter confined spaces unless adequately ventilated.

Storage

Do not apply direct flame to cylinder. Do not store cylinder in direct sun or expose it to heat above 120 F. Do not drop or refill this cylinder. Keep away from heat, sparks and flames.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls

Investigate engineering techniques to reduce exposures below airborne exposure limits. Provide ventilation if necessary to control exposure levels below airborne exposure limits (see below). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Eye / Face Protection

Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment available.

Skin Protection

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type glove material for given application. Rinse contaminated skin promptly. Wash contaminated clothing and clean protective equipment before reuse. Wash skin thoroughly after handling.

Respiratory Protection

Avoid breathing gas. Use NIOSH approved respiratory protection equipment appropriate to the material and/or its components (full facepiece recommended) when airborne exposure limits are exceeded (see below). Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Airborne Exposure Guidelines for Ingredients

Exposure Limit	Value
Chlorodifluoromethane	
ACGIH TWA -	1000 ppm 3540 mg/m3
Chloropentafluoroethane (CFC-115)	
ACGIH TWA -	6320 mg/m3 1000 ppm

-Only those components with exposure limits are printed in this section.

-Skin contact limits designated with a "Y" above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Odor	Colorless liquified gas with faint ether odor.
pH	NE
Specific Gravity	1.17 @ 30/0 C
Vapor Pressure	151.3 PSIA @ 70 F
Vapor Density	3.8
Melting Point	NE
Freezing Point	NE
Boiling Point	-45.6 C/ -50.1 F
Solubility In Water	Slight
Percent Volatile	100
Molecular Weight	86.48

10 STABILITY AND REACTIVITY

Stability

This material is chemically stable under specified conditions or storage, shipment and/or use. See HANDLING AND STORAGE section of this MSDS for specified conditions.

Incompatibility

Avoid contact with strong alkali or alkaline earth metals, finely powdered metals such as aluminum, magnesium or zinc and strong oxidizers, since they may react or accelerate decomposition.

Hazardous Decomposition Products

Thermal decomposition products include hydrogen fluoride, hydrogen chloride, carbon monoxide, carbon dioxide and chlorine.

11 TOXICOLOGICAL INFORMATION

Toxicological Information

Chlorodifluoromethane

There have been several accidental deaths associated with exposure to this material or mixtures with other fluorocarbons. Death was generally attributed to oxygen deficiency. Microscopic examination of the tissues of some of the victims showed effects on the lungs and fatty deposits in liver cells. An increase in the incidence of heart palpitations have been claimed by individuals occupationally exposed. Monitoring of workers during occupational exposure showed no connection to exposure and cardiac arrhythmia or neurologic disorders. Other epidemiological studies have reported similar results.

Repeated daily application of a 10 second spray caused reddening and slight swelling of the skin and a delay in hair growth. Skin allergy was not observed in guinea pigs following repeated exposure. Inhalation causes an initial stimulation and then depression of the central nervous system (CNS). Symptoms in animals include loss of equilibrium, tremors, convulsions and narcosis and death, usually attributed to asphyxiation. At levels that caused anesthesia, dogs exhibited convulsions. Exposure by inhalation at 300,000 to 400,000 ppm for 10-15 minutes was fatal to rabbits, also causing hemorrhages and effects on the liver. Following inhalation exposure to 50,000 ppm for 1 month, no effects were reported in guinea pigs, rats, dogs and cats; 60,000 ppm for 2-3 months elicited mild liver effects in rabbits; 5,000 ppm for 3 months caused no effects in dogs; 15,000 ppm for 4

11 TOXICOLOGICAL INFORMATION

months, produced no neurotoxic effects in rats; 14,000 ppm for 10 months produced effects on the lungs, CNS, heart, liver, kidney, spleen of rats, mice and rabbits, while at 2,000 ppm no effects were reported in rats and mice. An increase in malignant tumors of the salivary glands was reported in male rats but not in female rats or mice of either sex after inhalation exposure to 50,000 ppm 5 hr/day, 5 day/wk for 21 months. Long term inhalation of 5,000 ppm was not carcinogenic to rats and mice. Oral dosing for 52 weeks produced no adverse effects in rats. Inhalation at levels up to 50,000 and 100,000 ppm, produced no adverse effects on male reproductive performance in rats and mice respectively. Eye malformations were reported in rats exposed by inhalation during pregnancy at 50,000 ppm. In rats at 1,000 ppm or in rabbits exposed at levels up to 50,000 ppm. In rabbits, rats and humans, a small portion of inhaled material was distributed into the brain, heart, lungs, liver, kidneys and fat. It was rapidly eliminated from the body in the inhaled air. No significant metabolism occurs in humans or rats. The results of the tests for genetic changes were mixed. Studies with mice, dogs, rats, rabbits, cats and monkeys have shown that inhalation exposure can cause cardiac arrhythmias. The NOEL for cardiac sensitization in dogs is 25,000 ppm. Single exposure (acute) studies indicate:

Inhalation - Practically Non-Toxic (2 hr-LD50 = 300,000 (rat), 390,000 ppm (mouse))

Inhalation - Rat 10 min-EC50 = 140,000 ppm (CNS Effects)

Eye Irritation - Slightly Irritating to Rabbits (5-30 sec. exposure to gas spray)

Skin Irritation - (Moderate) Irritating to Rabbits (liquefied gas with patch applied)

Chloropentafluoroethane (CFC-115)

Human epidemiological studies did not show an association between exposure to this material and effects on nerve conduction velocities or effects on the heart.

No adverse effects were reported in rats following repeated oral dosing (2-weeks) of this material dissolved in corn oil at levels up to 172 mg/kg/day. Studies in dogs, rats, mice and monkeys indicate that under certain conditions, inhalation exposure to this material at high levels (100,000-200,000 ppm) can increase blood pressure and heart rate and cause other heart and respiratory effects. As with many other chlorofluorocarbons, inhalation of this material followed by intravenous injection of an agent to simulate human stress reactions, resulted in heart sensitization at high levels (150,000 ppm in dogs and 200,000 ppm in mice). No adverse effects were reported in mice following inhalation of this material alone at 100,000 ppm for 24-hours or in guinea pigs and rats following inhalation of 600,000 ppm for 2-hours. Longer-term inhalation (4-weeks) of high concentrations (200,000 ppm) was also without adverse effect in rats, guinea pigs or rats. Following inhalation of 100,000 ppm for 13-weeks, no deaths were reported in rats, female mice, rabbits or male dogs. Microscopic examination of the tissues of the rats and dogs did not indicate any treatment-related effects. This material produced no genetic changes in standard tests using animal or bacterial cells. It is rapidly eliminated from the bloodstream of dogs following inhalation exposure. Single exposure (acute) studies indicate

Inhalation - Practically Non-Toxic to Rats and Guinea Pigs (4-hr LC50 > 800,000 ppm)

12 ECOLOGICAL INFORMATION

Ecotoxicological Information

Chlorodifluoromethane

No effects were reported on the growth of aerobic and anaerobic microorganisms over a 24 hour period, including gram-positive and gram-negative species, from exposure to a media containing this material at 5 mg/ml.

Chemical Fate Information

Chlorodifluoromethane

12 ECOLOGICAL INFORMATION

The octanol/water partition coefficient (log Pow) was reported to be 1.08.

13 DISPOSAL CONSIDERATIONS

Waste Disposal

Recover, reclaim or recycle when practical. Dispose of in accordance with federal, state and local regulations. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

14 TRANSPORT INFORMATION

DOT Name	Chlorodifluoromethane and chloropentafluoroethane Mixture
DOT Technical Name	(R-502)
DOT Hazard Class	2.2
UN Number	UN 1973
DOT Packing Group	PG NA
RQ	

15 REGULATORY INFORMATION

Hazard Categories Under Criteria of SARA Title III Rules (40 CFR Part 370)

Immediate (Acute) Health	Y	Fire	N
Delayed (Chronic) Health	N	Reactive	N
		Sudden Release of Pressure	Y

The components of this product are all on the TSCA inventory list.

Ingredient Related Regulatory Information:

SARA Reportable Quantities

	CERCLA RQ	SARA TPQ
Chlorodifluoromethane	NE	

SARA Title III, Section 313

This product does contain chemical(s) which are defined as toxic chemicals under and subject to the reporting requirements of, Section 313 of Title III of the Superfund Ammendments and Reauthorization Act of 986 and 40 CFR Part 372. See Section 2

Chlorodifluoromethane

Chloropentafluoroethane (CFC-115)

Massachusetts Right to Know

This product does contain the following chemicals(s), as indicated below, currently on the Massachusetts Right to Know Substance List.

Chlorodifluoromethane

Chloropentafluoroethane (CFC-115)

Forane (R) 502
-Material Safety Data Sheet-
Elf Atochem North America, Inc.

New Jersey Right to Know

This product does contain the following chemical(s), as indicated below, currently on the New Jersey Right-to-Know Substances List.

Chlorodifluoromethane

Chloropentafluoroethane (CFC-115)

Pennsylvania Environmental Hazard

This product does contain the following chemical(s), as indicated below, currently on the Pennsylvania Environmental Hazard List.

Chlorodifluoromethane

Pennsylvania Right to Know

This product does contain the following chemical(s), as indicated below, currently on the Pennsylvania Hazardous Substance List.

Chlorodifluoromethane

Chloropentafluoroethane (CFC-115)

16 OTHER INFORMATION

Revision Information

Revision Date	17 JUL 1999	Revision Number	1
Supersedes Revision Dated	New Document		

Revision Summary

Initial Entry

Key

NE= Not Established NA= Not Applicable (R) = Registered Trademark

Elf Atochem North America, Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Elf Atochem, Elf Atochem expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.