



# Gas Burner Controls—Combination

VR8200 continued

\*TRADELINE models. • SUPER TRADELINE models.

Order Number	Inlet-Outlet Size (in.)	Capacity, A.G.A. Certified <sup>a</sup>		Pressure Regulator Setting		Type of Gas	Type of Pressure Regulator	Includes
		cfh	m <sup>3</sup> /hr	in. wc	kPa			
•VR8200A2124	½ x ½	130	3.7	3.5	0.87	Nat.	Standard	½ x ⅜ in. reducer bushing; 393690-14 bag assembly—¾ in. straight flange with O ring, screws and wrench; Q340 (36 in.) thermocouple with adapters; and 393691 Natural to LP gas conversion kit.
*VR8200A2132								½ x ⅜ in. reducer bushing; 393690-14 bag assembly—¾ in. straight flange with O ring, screws and wrench; and 393691 Natural to LP gas conversion kit.
<b>New!</b> •VR8200A2744								½ x ⅜ in. reducer bushing; 393690-14 bag assembly—¾ in. straight flange with O ring, screws and wrench; and 393691 Natural to LP gas conversion kit; also includes ¾ in. angle flange.
<u>VR8200C1041</u>				0.9 Step <sup>b</sup> ; 3.5 full rate	0.22 Step <sup>b</sup> ; 0.87 full rate		Step-opening	—
<u>VR8200C1074</u>				1.4 Step <sup>b</sup> ; 10.0 full rate	0.35 Step <sup>b</sup> ; 2.5 full rate	LP		
<u>VR8200C1082</u>				2.5 Step <sup>b</sup> ; 10.0 full rate	0.62 Step <sup>b</sup> ; 2.5 full rate			
<u>VR8200C1090</u>				5.5 Step <sup>b</sup> ; 10.0 full rate	1.37 Step <sup>b</sup> ; 2.5 full rate			
* <u>VR8200H1251</u>				3.5	0.87	Nat.	Slow Opening	½ x ⅜ in. reducer bushing; 393690-14 bag assembly—¾ in. straight flange with O ring, screws and wrench; and 393691 Natural to LP gas conversion kit.
<u>VR8200P1039</u>				0.9 Step <sup>b</sup> ; 3.5 full rate	0.22 Step <sup>b</sup> ; 0.87 full rate		Step-opening	—
<u>VR8200P1047</u>				2.5 Step <sup>b</sup> ; 10.0 full rate	0.62 Step <sup>b</sup> ; 2.5 full rate	LP		

<sup>a</sup> Capacity based on 1000 Btu/ft<sup>3</sup>, 0.64 sp gr natural gas at 1 in. wc pressure drop (37.3 MJ/m<sup>3</sup>, 0.64 sp gr natural gas at 0.25 kPa pressure drop).

<sup>b</sup> Step pressure is not adjustable.